Journal of Advancements in Material Engineering
Volume 1 Issue 3

Relationship between Loss factor and Fracture strength Viscoelastic Materials

Anuradha majumder

Faculty of Engineering, Materials Engineering Department, Calcutta Institute of Engineering and Management, ChandiGhosh Road, Tollygunge, Kolkata.

majumder.anukol@gamil.com

Abstract

Fiber-fortified composites are utilized as a part of numerous present applications because of their uniqueness, and the capacity to give distinct properties to fulfill fundamental prerequisites. In the same way as other different materials composites are inclined to imperfections, which may radically debase their material properties. Along these lines, to ensure that imperfections are neither present, nor are sufficiently extreme to trade off execution of the material, fiber-fortified composites ought to be tried both earlier, and amid the life of the segment. Delamination between layers is an imperative issue in uses of fiber strengthened composite overlays. Tests were completed to decide the break strength of composite overlays utilizing blended mode bowing tests, yet this strategy is dangerous. In this study, relationship between vibration damping and break strength in polymeric composite overlaid was reenacted with the goal that Vibration damping test can be utilized as none dangerous test (NDT) to decide crack durability of composites with no harm of test.

Keywords: *none dangerous test (NDT), vibration damping, overlaid carbon/epoxy composite, break durability.*

INTRODUCTION

Fiber fortified composite overlay are turning into a more imperative piece of day by day life. Due to such material qualities, for example, high return quality and low weight, composites are utilized as a part of basic segments of parts. Furthermore, propensity for dependable non damaging testing methods increments to give the persevering composite specimen, and imagine a scenario in which any deformities are available in the material that could bring about disappointment amid. The life of the

part.Fiber fortified composite's mind boggling structure cause to numerous types of testing as of now utilized to test metal segments out of date furthermore they are dangerous. The production of dependable basic overlay composites for space applications requires exactness outline and producing utilizing a coordinated, simultaneous building approach. Since the last material attributes are set up in the meantime the part or subassembly is manufactured, part plan, creation improvement and material portrayal must continue simultaneously. Since composite materials are exceptionally custom fitted to meet auxiliary prerequisites of the get together, stringent in-procedure controls are required to touch base at an arrangement with ideal physical and material properties.

adaptability, expanded quality to weight proportion, dimensional steadiness under warm stacking, light weight, simplicity of manufacture and establishment, erosion resistance, sway resistance, high weakness quality (contrasted with metal structures with the same measurements), furthermore, item effortlessness when contrasted with customary manufactured metal structures [1]. Like other material composites inclined to abandons and inter laminar delamination is a typical and possibly perilous method of disappointment in composite structures. Delamination regularly brings about the loss of solidness and quality, which may prompt wellbeing and dependability issues. Undetected subsurface delamination can prompt calamitous disappointments with no outside signs. This makes delamination a noteworthy obstruction in accomplishing the full weight sparing capability of cutting edge composite materials [2, 3]. Delamination in composites is regularly a mixed mode break. Both interlaminar malleable and shear anxieties can be available at the delamination front. Interlaminar malleable burdens offer ascent to mode I crack while interlaminar shear stresses result in mode II breaks. Utilizing break mechanics to portray the onset and development of delamination has turned into a by and large acknowledged hone. The crack strength of materials can be measured by the basic vitality discharge rate GIc for unadulterated mode I and GIIc for immaculate mode II. While mode I break rules the disappointment in isotropic materials, the cooperation of shear and malleable break convolutes the instrument of disappointment in composite materials.

Delamination resistance of a composite cover under mode I break is not quite the same as the delamination
resistance under mode II break. The instrument of break additionally shifts with the proportion of the distinctive methods of breaks included [2, 4–6]. This communication of shear and elastic breaks confuses the component of disappointment in composite materials [3, 7–9].

Damping is the capacity of a material to oppose vibration. The three most normal kind of damping are gooey, coulomb and hysteresis [10,11]. All the three sorts of damping disseminate vitality amid the vibration and amongthem gooey damping and coulomb damping rely on upon vibrating limit conditions (geometries, frequencies, and so forth.) and also the vibrating material themselves, though hysteresis damping depends just on the vibrating materials and is free of limit conditions, thus hysteresis damping is not just connected in vibration control, additionally has the capacity to portray material attributes, for example, inborn property. The misfortune element, η, is a standout amongst the regularly utilized terms to assess damping capacity of a material and there are a ton of strategies to compute misfortune component which they are taking after:

- complex modulus documentation
- complex solidness documentation
- logarithmic decrement strategy
- hysteresis circle strategy
- strain vitality strategy
- half power band width strategy

By looking into the meaning of the break sturdiness it gets clear that if the crack durability of a material raises, the measure of mechanical vitality that the material stores before crack, increments. Then again, the misfortune component η which assesses damping ability of the material, demonstrates the measure of vitality that the material stores amid damping. Accordingly both crack sturdiness and misfortune variable identify with the measure of mechanical vitality that the material can store and there ought to be an intelligent connection between these two material properties. In request to discover this relationship, review upper strategies and with respect to nature mechanical properties of fiber strengthened composite overlay, mode II (unadulterated shear) was chosen to confirm break sturdiness of composite and half power band width technique was wanted to decide misfortune component as damping property of composite, as a last point was characterized the relationship between break strength and misfortune element.

Result and exchange

As indicated by bend of connected burden versus opening dislodging, misfortune element and break durabilitywere resolved graphically. In this strategy, misfortune variable and crack sturdiness were gotten roughly also, some bend respects right line, to figure territory under power dislodging bend, this region partitioned to two or all the more part with straightforward geometry, for example, rectangular or triangle. Figure 1 demonstrates the connected burden versus opening

dislodging bend of the example.



Fig 1. *Curve of load and displacement of laminated carbon*

in figure 2 shows the loading path, when the load increase to maximum level at point A the crack begins to propagation and the load coming to decrease until point B. to obtain the affiliation between loss factor and fracture toughness loading path and unloading path were assumed linear, but this theory related to elastic material, whereas composite laminate is viscoelastic material, so loading path and unloading path suppose as a curve, however to calculate the loss factor and affiliation between loss factor and fracture toughness, the shaded area of OA curve was assuming 0.001 of area under OA line.



Fig2. *Relationship between fracture toughness and loss factor of laminated carbon/ epoxy composite*

Finally according to the fig 2, the fracture toughness of composite carbon/epoxy during working hour can be obtained by using nondestructive system such as ultrasonic pulse- echo, eddy current and impulse frequency response technique, to determine loss factor η and then fracture toughness was calculated from fig.2. Really, this method is a nondestructive method to measurement fracture toughness of laminated carbon/ epoxy composite. Finally must be founded that these results are completely similar to some literature in this field [11].

CONCLUSION

Some measurement methods of fracture toughness are destructive and they are not using during work of composite, so in this paper the relationship between loss factor and fracture toughness in viscoelastic materials was modeling, then Using NDT technique such as ultrasonic pulse- echo, eddy current and impulse frequency response technique, to achieve loss factor and then fracture toughness was calculated from relationship between η and GIIC that was drawn as curve.

REFERENCE

1. NASA, Structural laminate composites for space application, practices No. PD-ED-1217 P. 1-8.
2. Garg AC. Delaminations – a damage mode in composite structures. EngFractMech 1988; 29(5):557–84.

3. O'Brien TK. Mixed-mode strain-energy release rate effects on edge delamination of composites.Effects of defects in composite materials. ASTM STP, vol. 836. American Society for Testing and Materials; 1984. p. 125–142.
4. O'Brien TK. Composite interlaminar shear fracture toughness, GIIc: shear element or sheer myth? In: Bucinell RB, editor. Composite materials: fatigue and fracture – seventh volume. ASTM STP, vol.1330. American Society for Testing and Materials; 1998. p. 3–18.
5. Reeder JR, Crews Jr JH. Nonlinear analysis and redesign of the mixed-mode bending delamination test. NASA Technical Memorandum 102777; 1991.
6. Benzeggagh ML, Kenane M. Measurement of mixed-mode delamination fracture toughness of unidirectional glass/epoxy composites with mixed-mode bending apparatus. Compos Sci Technol1996;56:439–49.
7. O'Brien TK. Characterization of delamination onset and growth in a composite laminate. In: ReifsniderKL, editor. Damage in composite materials. ASTM STP, vol. 775. American Society for Testing and Materials; 1984. p. 140–67.
8. Law GE. A mixed-mode fracture analysis of (±25/90n)s graphite/ epoxy composite laminates. Effects of defects in composite materials. ASTM STP, vol. 836. American Society for Testing and Materials;1984. p. 143–160.
9. Lee SM. Failure mechanisms of edge delaminations of composites. J Compos Mater 1990;24:1200–12.
10. Gibson.R.F et al, The Use of Nondestructive Damping Measurement to Characterize Interlaminar Fracture Toughness in Composite Laminates, SEM Conference, Maryland, USA, 1994.
11. Zhao. H, "The use of none destructive damping measurement to characterize interlaminarfracturetoughness in polymer composite materials", dissertation of doctoral,Wayne State University, 1997.
12. Mary J. Mathews, Stephen R. Swanson. Characterization of the interlaminar fracture toughness of alaminated carbon/epoxy composite, Composites Science and Technology 67 (2007) 1489–1498.